

Curved Glass Deli Case KDG Series

KDG-36 | KDG-48 KDG-60 | KDG-72

Features

- Stainless steel SS304 exterior with coated metal interior trim
- Digital temperature control with 35°-41°F holding range
- Equipped with 4 casters (2 with brakes)
- Comes standard with 2 adjustable shelves
- Double-glazed, tempered safety glass curved front and sides
- Auto defrost system for front glass and rear door frame
- Gravity coil refrigeration system delivers reliable preservation of food products
- LED lighting on sides and top
- Slide-out condensing unit for easy maintenance
- Ozone friendly R290 refrigerant
- ETL approved (conforms to UL-471 and NSF-7)
- DOE2017 energy standard compliant











Nema 5-15P Dedicated Circuit

Project Name:						
Location:						
Item:	Qty:					
Model:						





3560 NW 56th Street Fort Lauderdale, FL, United States Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100 5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Telephone: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com




Curved Glass Deli Case KDG Series

KDG-36 | KDG-48 KDG-60 | KDG-72







Model	Doors	Capacity (cu.ft)	Shelves	Cabinet Dimesions (Inches / mm)		НР	Voltage	Amps	Cord Length	Net Weight	
				W	D	н				(ft.)	(lbs. / <i>kg</i>)
KDG-36	2	12	2	35.6" <i>900</i>	32.5" <i>825</i>	48.2 " <i>1150</i>	1/3	110V/60Hz	4.50	6	410 <i>186</i>
KDG-48	2	18	2	47.7" 1200	32.5" <i>825</i>	48.2 " <i>1150</i>	1/3	110V/60Hz	5.00	6	496 <i>225</i>
KDG-60	2	21.5	2	59" <i>1500</i>	32.5" <i>825</i>	48.2 " 1150	3/5	110V/60Hz	5.80	6	573 260
KDG-72	2	26.4	2	70.9" <i>1800</i>	32.5" <i>825</i>	48.2 " <i>1150</i>	3/4	110V/60Hz	6.40	6	650 <i>295</i>

The refrigerated KDG series cases are engineered to operate in locations not exceeding 80°F and 55% relative humidity.

